



Cross section (mm<sup>2</sup>) / number of conductors simultaneously connectable to the terminal

	Type	In [A]	Torque [Nm]		Cross section (mm <sup>2</sup> ) / number of conductors simultaneously connectable to the terminal															
					1,5	2,5	4	6	10	16	25	35	50	70	95	120	150	185	240	300
GKL	1x50*	160	5Nm (2,5-16mm <sup>2</sup> )	Al	-	1	1	1	1	1	1	1	1	-	-	-	-	-	-	
			10Nm (25-50mm <sup>2</sup> )	Cu	-	3	3	3	3	2	1	1**	1	-	-	-	-	-	-	-
	2x50*	200	5Nm (2,5-16mm <sup>2</sup> )	Al	-	1	1	1	1	1	1	1	1	-	-	-	-	-	-	-
			10Nm (25-50mm <sup>2</sup> )	Cu	-	3	3	3	3	2	1	1**	1	-	-	-	-	-	-	-
	1x95*	200	12Nm (16-50mm <sup>2</sup> )	Al	-	-	-	-	-	1	1	1	1	1	1	-	-	-	-	-
			22Nm (70-95mm <sup>2</sup> )	Cu	-	-	-	-	-	3	2	2	1	1**	1	-	-	-	-	-
	2x95*	400	12Nm (16-50mm <sup>2</sup> )	Al	-	-	-	-	-	1	1	1	1	1	1	-	-	-	-	-
			22Nm (70-95mm <sup>2</sup> )	Cu	-	-	-	-	-	3	2	2	1	1**	1	-	-	-	-	-
	1x150*	250 320	12Nm (25-50mm <sup>2</sup> )	Al	-	-	-	-	-	-	-	1	1	1	1	1	1	1	-	-
			22Nm (70-95mm <sup>2</sup> )	Cu	-	-	-	-	-	-	-	3	3	2	1	1	1**	1	-	-
			38Nm (120-150mm <sup>2</sup> )																	
	2x150*	500 640	12Nm (25-50mm <sup>2</sup> )	Al	-	-	-	-	-	-	-	1	1	1	1	1	1	1	-	-
			22Nm (70-95mm <sup>2</sup> )	Cu	-	-	-	-	-	-	-	3	3	2	1	1	1**	1	-	-
			38Nm (120-150mm <sup>2</sup> )																	
	1x240*	315	25Nm (35-120mm <sup>2</sup> )	Al	-	-	-	-	-	-	-	-	1	1	1	1	1	1	1	1
			55Nm (150-240mm <sup>2</sup> )	Cu	-	-	-	-	-	-	-	-	-	3	3	2	1	1	1	1**
2x240*	630	25Nm (35-120mm <sup>2</sup> )	Al	-	-	-	-	-	-	-	-	1	1	1	1	1	1	1	1	
		55Nm (150-240mm <sup>2</sup> )	Cu	-	-	-	-	-	-	-	-	-	3	3	2	1	1	1	1**	1

\* N = Blue = only for one neutral conductor

\* PE = Yellow/green = only for one protective conductor

\*\* Biggest fine-strand conductors

Cu conductors may be solid, multi-strand or fine-strand conductors. With fine strand conductors use of cable end sleeve is recommended but not required.